

Leaflet

Digital artwork for flexo printing (Version 1.0 / March 2020)

Data exchange:

As attachment via e-mail tobias.maienfisch@primcut.ch, download-link or WeTransfer.

Software

We always work with the latest versions of *ArtPro, Illustrator, Photoshop, In Design* and *Acrobat Professional*.

Data:

We prefer open data, as this allows us to adapt and modify technical requirements to the specifications of flexo printing (colour structure, colour overlaps, ...).

PDF:

Please send us .pdf files Version 1.6

Fonts:

Enclose all fonts used, or convert them into paths or vector data.

Spot colors:

Please create spot colors according to the PANTONE Color Matching System.

Pictures:

We need at least 300 lpi resolution on the final format. If possible, supplie us with the original *Photoshop* files with layers.

Trapping:

Please don't do trapping. We create these ourselves.

Barcodes:

For barcodes, please indicate code type, size and number.

The barcode should not be smaller than 80%.

Fontsize:

Positive: Minimum 3 Points, negative Minimum 4 Points.

Line size:

Positive lines: Minimum 0.07mm, negative lines: Minimum 0.1mm.

Control printout:

If available, please send us a colour-consistent proof, this is our guideline. Laserprints or other print-outs are only for visual control and are not colour-consistent. On request, we will send you a final proof for approval.

> Primcut AG Toggenburgerstrasse 42 CH-9652 Neu St. Johann